



GG 010 LOADER ARTICULATED

The GG010 model is equipped with a three-cylinder, inline, liquid-cooled diesel engine Changchai 390. The engine delivers a rated power of 25 HP and a rated speed of 2400 rpm, providing adequate power for performing a variety of tasks. Thanks to this power, the machine is capable of handling demanding work conditions while offering economical operation.

The GG010 is equipped with a 0.5 m³ bucket with a width of 1600 mm. The maximum breakout force is 28 kN, allowing for effective material handling. The rated load capacity is 1000 kg, and the operating weight is 2850 kg, making the machine powerful and stable enough to meet the demands of work in various conditions. The minimum turning radius is 4600 mm, allowing for precise maneuvers in tight spaces.

■ Specification

| | |
|-----------------|---|
| Engine type | Inline, liquid-cooled, three-cylinder diesel engine |
| Rated power | 25 HP |
| Steering system | Full hydraulic |
| Brakes | Four-wheel hydraulic brake |
| Tires | 10-16,5 |
| Track | 1285 mm |
| Engine model | Changchai 390 |
| Rated speed | 2400 rpm |
| System pressure | 10 Mpa |
| Parking brake | Manual operation |
| Wheelbase | 2170 mm |

■ Working Range

| | |
|------------------------|--------------------|
| Bucket capacity | 0,5 m ³ |
| Max. breakout force | 28 kN |
| Operating weight | 2850 kg |
| Minimum turning radius | 4600 mm |
| Bucket width | 1600 mm |
| Rated load capacity | 1000 kg |
| Drive | Four-wheel drive |
| Dumping height | 2560 mm |

■ Main Dimensions

| | |
|---------------------------------------|---------|
| Overall length (bucket on the ground) | 4100 mm |
| Overall height | 2530 mm |
| Overall width | 1600 mm |

■ Additional equipment (for reference)

| | |
|---|--------------------------|
|  | 4-in-1 Bucket |
|  | Grapple (Crocodile-type) |
|  | Pallet Forks |
|  | Auger |
|  | Bale Grab |
|  | Snow Plow |
|  | Mower |
|  | Sweeper |

