



GG013

ARTICULATED LOADER

The GG013 is equipped with a four-cylinder liquid-cooled diesel engine with a rated power of 50 HP. The rated speed is 2200 rpm, providing sufficient power for loading and transportation tasks. The steering system is fully hydraulic, ensuring precise control of the machine. The all-wheel-drive system allows the machine to handle difficult terrain, providing adequate traction and stability in any conditions.

The GG013 is characterized by high working efficiency. The bucket capacity is 0.4 m³, and the bucket width is 1600 mm, allowing for effective material loading and transportation. The maximum lifting force is 28 kN, making the machine capable of handling various materials and suitable for work in various industries. The machine's payload capacity is 1300 kg, allowing for the transfer and loading of large amounts of materials while maintaining full stability.

■ Specification

Engine Type	Inline, liquid-cooled, four-cylinder diesel engine
Rated Speed	2200 rpm
System Pressure	10 Mpa
Parking Brake	Hand-operated
Wheelbase	2170 mm
Rated Power	50KM
Steering System	Full hydraulic
Brakes	Four-wheel hydraulic brake
Tires	10-16,5
Track	1285 mm


■ Work Range

Bucket Capacity	0,4 m3
Max. Force	28 KN
Machine Weight	3700 kg
Min. Turning Radius	4600 mm
Bucket Width	1600 mm
Load Capacity	1300 kg
Drive	Four-wheel drive
Dump Height	2950 mm

■ Main Dimensions

Total Length (Bucket on the ground position)	5200 mm
Total Height	2700 mm
Total Width	1720 mm

■ Additional equipment (for reference)



4-in-1 Bucket



Grapple (Crocodile-type)



Pallet Forks



Auger



Bale Grab



Mower



Snow Plow



Sweeper

