



GG04

MINI LOADER

The vehicle is equipped with a bucket with a capacity of 0.15 m³ and a load capacity of 400 kg. Thanks to this, the GG04 is an ideal solution for loading and unloading materials in various industries, such as construction or agriculture. The bucket enables easy handling even in narrow and hard-to-reach areas.

The loader is equipped with a Briggs & Stratton engine featuring two cylinders and air cooling. This type of engine ensures reliability and high power, while the air cooling system makes the engine resistant to overheating, which is crucial during prolonged operation in varying weather conditions. Gasoline-powered, the loader is ready to work in all environments.

■ Specification

Machine Weight	800 kg
Number of Cylinders	2
Drive	Gasoline
Minimum Height	1270 mm
Bucket Load Capacity	400 kg
Hydraulic Pump	Parker
Engine Displacement for Walking Mechanism	BM5-375 ml
Rated Power	17 kw
Tire Specifications	18*8.50-8
Fuel Tank Capacity	20 L
Engine Model	Briggs Stratton
Cooling Method	Air-cooled
Maximum Height	2400 mm
Bucket Capacity	0.15 m ³
Nominal Pressure	18 Mpa
Hydraulic Pump Flow Rate (L/min)	15+15+15 l/min
Distributor	Italy M45
Engine Oil Capacity	1.7 L
Hydraulic Oil Tank Capacity	25 L

■ Main Dimensions

Length	2230 mm
Height	1300 mm
Width	1150 mm
Wheelbase	640 mm
Bucket Width	1150 mm
Maximum Slope for Operation	25%
Ground Clearance	100 mm

■ Operating Range

Maximum Loading Height	2080 (mm)
Rated Speed	3200 (r/min)
Maximum Unloading Height	1950 (mm)

■ Additional equipment

Forks bucket
Grab bucket
4-in-1 bucket
Chain trencher
Snow plow
Pallet fork
Grading scraper



