



GG04G

MINI LOADER

The vehicle is equipped with a bucket with a capacity of 0.15 m³ and a load capacity of 300 kg. Thanks to this, the GG04G is an ideal solution for loading and unloading materials in various industries, such as construction or agriculture. The bucket enables easy handling even in narrow and hard-to-reach areas.

The GG04G mini loader features a hydraulic system with a nominal pressure of 18 MPa, providing adequate power for material handling. The integrated Parker hydraulic pump with a flow rate of 15 + 15 + 15 L/min, combined with the Italy M45 distributor, allows for precise control of the hydraulic system, enhancing work efficiency in demanding conditions.

■ Specification

Engine Model	Briggs Stratton
Number of Cylinders	2
Cooling Method	Air cooling
Displacement	627 cm ³
Drive	Gasoline
Hydraulic Pump Capacity	505 ml/rev
Travel Motor Displacement	375 ml
Fuel Tank Capacity	19,9 L
Rated Speed	3200 obr./min
Machine Weight	800 kg
Rated Power	17 kW
Engine Oil Capacity	1,7 L
Rated Pressure	18 Mpa
Hydraulic Pump Flow Rate	16 l/min
Hydraulic Tank Capacity	25,8 L
Bucket Load Capacity	300 kg

■ Main Dimensions

Length	2230 mm
Height	1300 mm
Width	1160 mm
Wheelbase	640 mm
Track Width	900 mm
Ground Clearance	100 mm

■ Operating Range

Maximum Loading Height	2080 mm
Maximum Height	2400 mm
Bucket Capacity	0,15 m ³
Maximum Unloading Height	1950 mm
Minimum Height	1270 mm
Gradeability	25%

■ Additional equipment

Forks bucket	
Grab bucket	
4-in-1 bucket	
Chain trencher	
Snow plow	
Pallet fork	
Grading scraper	

