



GG09

ARTICULATED LOADER

With an engine power of 24.47 HP and 4 cylinders, the GG09 guarantees reliable performance, reaching a maximum speed of up to 12 km/h. The 0.5 m³ bucket, with a maximum reach of 603 mm, enables quick and easy loading and unloading. The lifting height of 2750 mm ensures the GG09 can handle a wide range of tasks, from material transport to working in tough terrain.

The GG09 loader is not only efficient but also durable – its weight of 2300 kg and compact dimensions (length with lowered bucket 4067 mm and overall width 1451 mm) make it ideal for work in both narrow spaces and more open areas. Additionally, the modern design ensures ease of operation, attention to detail, and exceptional durability, guaranteeing years of reliable service. The GG09 is known for its stability, with a ground clearance of 351 mm and a wheelbase 1595 mm.

■ Specification

Load Capacity	900 kg
Nominal Engine Power	24.47 KM
Nominal Speed	2400 r/min
Engine	Kubota Euro 5 (V1505)
Number of Cylinders	4
Machine Weight	2300 kg

■ Working Range

Travel Speed	12 km/h
Lifting Height	2750 mm
Bucket Tilt Angle at Maximum Height	51.2 °
Descent Angle	20.75 °
Bucket Width	1650 mm
Dump Reach at Full Height	603 mm
Bucket Capacity	0.5 m ³
Bucket Tilt Angle During Transport	51.2 °
Maximum Dump Angle at Full Height	38.8 °
Ground Clearance	351 mm
Ground Clearance During Dumping at Full Height	2707 mm

■ Dimensions

Length with Lowered Bucket	4067 mm
Overall Width	1451 mm
Length from Rear Axle to Bucket Tip	3085 mm
Turning Radius Outside Tires	3054 mm
Overall Height	2410 mm
Wheelbase	1595 mm
Turning Radius with Load	3375 mm

■ Additional equipment (for reference)



4-in-1 Bucket



Grapple (Crocodile-type)



Pallet Forks



Auger



Bale Grab



Mower



Snow Plow



Sweeper

